

MATERIAL SAFETY DATA SHEET

West System Inc.

West System Inc.

Page 2 of 4

WEST SYSTEM® SIX 10 RESIN

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WEST SYSTEM® SIX 10 RESIN
PRODUCT CODE: 810A
CHEMICAL FAMILY: Epoxy Resin
CHEMICAL NAME: Modified bisphenol A based epoxy resin.
FORMULA: Not applicable.

MANUFACTURER:

West System Inc.
102 Patterson Ave.
Bay City, MI 48706, U.S.A.
Phone: 866-937-8797 or 989-684-7286
www.westsystem.com

EMERGENCY TELEPHONE NUMBERS:

Transportation
CHEMTREC: 800-424-9300 (U.S.)
703-527-3887 (international)
Non-transportation
Poison Hotline: 800-222-1222

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION
Bisphenol-A type epoxy resin	25085-99-8	> 50%
Aliphatic glycidyl ether		< 20%
Bisphenol-F type epoxy resin	28064-14-4	< 20%
1,3-Bis(2,3-epoxypropoxy)-2,2-dimethylpropane		< 10%

(This product contains various filler powders in concentrations >1% that are regulated only as nuisance dusts. In this product they do not present a health hazard and consequently are not identified in this section.)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS Hazard Rating: Health - 2 Flammability - 1 Physical Hazards - 0

WARNING! Irritant. May cause allergic skin response in certain individuals. May cause moderate irritation to the skin. Clear gel with mild odor.

PRIMARY ROUTE(S) OF ENTRY: Skin contact.

POTENTIAL HEALTH EFFECTS:

ACUTE INHALATION: Not likely to cause acute effects unless heated to high temperatures. If product is heated, vapors generated can cause headache, nausea, dizziness and possible respiratory irritation if inhaled in high concentrations.

CHRONIC INHALATION: Not likely to cause chronic effects. Repeated exposure to high vapor concentrations may cause irritation of pre-existing lung allergies and increase the chance of developing allergy symptoms to this product.

ACUTE SKIN CONTACT: May cause allergic skin response in certain individuals. May cause moderate irritation to the skin such as redness and itching.

CHRONIC SKIN CONTACT: May cause sensitization in susceptible individuals. May cause moderate irritation to the skin.

EYE CONTACT: May cause irritation.

INGESTION: Low acute oral toxicity.

SYMPTOMS OF OVEREXPOSURE: Possible sensitization and subsequent allergic reactions usually seen as redness and rashes. Repeated exposure is not likely to cause other adverse health effects.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin and respiratory disorders may be aggravated by exposure to this product. Pre-existing lung and skin allergies may increase the chance of developing allergic symptoms to this product.

4. FIRST AID MEASURES:

FIRST AID FOR EYES: Flush immediately with water for at least 15 minutes. Consult a physician.

FIRST AID FOR SKIN: Remove contaminated clothing. Wipe excess from skin. Remove with waterless skin cleaner and then wash with soap and water. Consult a physician if effects occur.

FIRST AID FOR INHALATION: Remove to fresh air if effects occur. Consult a physician.

FIRST AID FOR INGESTION: No adverse health effects expected from amounts ingested under normal conditions of use. Seek medical attention if a significant amount is ingested.

5. FIRE FIGHTING MEASURES:

FLASH POINT: >200°F (Tag Closed Cup)

EXTINGUISHING MEDIA: Foam, carbon dioxide (CO₂), dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear a self-contained breathing apparatus and complete full-body personal protective equipment. Closed containers may rupture (due to buildup of pressure) when exposed to extreme heat.

FIRE AND EXPLOSION HAZARDS: HAZARDOUS DECOMPOSITION PRODUCTS: During a fire, smoke may contain the original materials in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include, but are not limited to: phenolics, carbon monoxide, carbon.

6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES: Soak up in absorbent material or scrape up. Residual can be removed with non-flammable solvent, but solvent should be used sparingly and with appropriate precautions.

7. HANDLING AND STORAGE:

STORAGE TEMPERATURE (MIN/MAX): 40°F (4°C) / 120°F (49°C)

SHELF LIFE: Reference product label.

STORAGE: Store in cool, dry place. Store in tightly sealed containers to prevent moisture absorption and loss of volatiles. Excessive heat over long periods of time will degrade the resin.

HANDLING PRECAUTIONS: Avoid prolonged or repeated skin contact. Wash thoroughly after handling. Launder contaminated clothing before reuse. Avoid inhalation of vapors from heated product. Precautionary steps should be taken when curing product in large quantities. When mixed with epoxy curing agents this product causes an exothermic, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

EYE PROTECTION GUIDELINES: Safety glasses with side shields or chemical splash goggles.

SKIN PROTECTION GUIDELINES: Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

RESPIRATORY/VENTILATION GUIDELINES:

Good room ventilation is usually adequate for most operations. Wear a NIOSH/MSHA approved respirator with an organic vapor cartridge whenever exposure to vapor in concentrations above applicable limits is likely.

Note: Pro-Set, Inc., has conducted an air sampling study using this product or similarly formulated products. The results indicate that the components sampled for (epichlorohydrin, ethylene glycol monobutyl ether) were either so low that they were not detected at all or they were well below OSHA's permissible exposure levels.

ADDITIONAL PROTECTIVE MEASURES: Practice good caution and personal cleanliness to avoid skin and eye contact. Avoid skin contact when removing gloves and other protective equipment. Wash thoroughly after handling. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

MSDS #610A-08a

Last Revised: 09SEPT08

MSDS #610A-08a

Last Revised: 09SEPT08

OCCUPATIONAL EXPOSURE LIMITS: Not established for product as whole. Refer to OSHA's Permissible Exposure Level (PEL) or the ACGIH Guidelines for information on specific ingredients.

9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL FORM: Gel.
COLOR: Colorless.
ODOR: Mild.
BOILING POINT: > 400°F.
MELTING POINT/FREEZE POINT: No data.
VISCOSITY: Approx. 100,000 centipoise.
pH: No data.
SOLUBILITY IN WATER: Slight.
SPECIFIC GRAVITY: 1.17.
BULK DENSITY: 9.75 pounds/gallon.
VAPOR PRESSURE: < 1 mm-Hg @ 20°C.
VAPOR DENSITY: Heavier than air.
% VOLATILE BY WEIGHT: The Volatile Matter Content of this two-component system was determined by mixing the individual components together at the proper ratio. Refer to the hardener's MSDS for information about the total volatile content of the resin/hardener system.

10. REACTIVITY:

STABILITY: Stable.
HAZARDOUS POLYMERIZATION: Will not occur by itself, but a mass of more than one pound of product plus an aliphatic amine will cause irreversible polymerization with significant heat buildup.
INCOMPATIBILITIES: Strong acids, bases, amines and mercaptans can cause polymerization.
DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide fumes may be produced when heated to decomposition.

11. TOXICOLOGICAL INFORMATION:

No specific oral, inhalation or dermal toxicology data is known for this product. Specific toxicology information for a bisphenol-A based epoxy resin present in this product is indicated below:

Oral: LD₅₀ > 5000 mg/kg (rats)
Inhalation: No Data.
Dermal: LD₅₀ = 20,000 mg/kg (skin absorption in rabbits)

TERATOLOGY: Ethylene glycol monobutyl ether (present at < 0.5 %) causes harm to the fetus in laboratory animal studies. Harm to the fetus occurs at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

MUTAGENICITY: Neopentyl glycol diglycidyl ether has been reported to be mutagenic in some laboratory tests.

CARCINOGENICITY:

NTP: Product not listed.
IARC: Product not listed.
OSHA: Product not listed.

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol-A. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic. Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen.

Epichlorohydrin, an impurity in this product (<25 ppm) has been reported to produce cancer in laboratory animals and to produce mutagenic changes in bacteria and cultured human cells. It has been established by the International Agency for Research on Cancer (IARC) as a probable human carcinogen (Group 2A) based on the following conclusions: human evidence – inadequate; animal evidence – sufficient. It has been classified as an anticipated human carcinogen by the National Toxicology Program (NTP). Note: It is unlikely that normal use of this product would result in measurable exposure concentrations to this substance.

Neopentyl glycol diglycidyl ether has been reported to be carcinogenic in some laboratory tests.

12. ECOLOGICAL INFORMATION:

Prevent entry into sewers and natural waters. May cause localized fish kill.

13. DISPOSAL CONSIDERATIONS:

WASTE DISPOSAL METHOD: Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION:

D.O.T. SHIPPING NAME: Not regulated by DOT.
TECHNICAL SHIPPING NAME: Not applicable.
D.O.T. HAZARD CLASS: Not applicable.
U.N./N.A. NUMBER: Not applicable.
PACKING GROUP: Not applicable.

15. REGULATORY INFORMATION:

OSHA STATUS: Slight irritant; possible sensitizer.
TSCA STATUS: All components are listed on TSCA inventory or otherwise comply with TSCA requirements.
SARA TITLE III:
SECTION 313 TOXIC CHEMICALS: None (de minimus).

STATE REGULATORY INFORMATION:

The following chemicals are specifically listed or otherwise regulated by individual states. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME /CAS NUMBER	CONCENTRATION	STATE CODE
Epichlorohydrin 106-89-8	< 5ppm	CA
Phenyl glycidyl ether 122-60-1	< 5ppm	CA
Ethylene glycol monobutyl ether 111-76-2	< 0.5%	NJ, PA

¹ These substances are known to the state of California to cause cancer or reproductive harm, or both.

16. OTHER INFORMATION:

REASON FOR ISSUE: New product.
PREPARED BY: G.M. House
APPROVED BY: G.M. House
TITLE: Health, Safety & Environmental Manager
APPROVAL DATE: September 9, 2008
SUPERSEDES DATE: NA
MSDS NUMBER: 610A-08a

Note: The Hazardous Material Indexing System (HMIS), cited in the Emergency Overview of Section 3, uses the following index to assess hazard rating: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; and 4 = Severe.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of West System Inc. The data on this sheet is related only to the specific material designated herein. West System Inc. assumes no legal responsibility for use or reliance upon these data.

MATERIAL SAFETY DATA SHEET

West System Inc.

West System Inc.

Page 2 of 4

WEST SYSTEM® SIX 10 Hardener

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WEST SYSTEM® SIX 10 Hardener
PRODUCT CODE: 610B
CHEMICAL FAMILY: Amine.
CHEMICAL NAME: Modified polyamine.
FORMULA: Not applicable.

MANUFACTURER:
West System Inc.
102 Patterson Ave.
Bay City, MI 48706, U.S.A.
Phone: 866-937-8797 or 989-684-7286
www.westsystem.com

EMERGENCY TELEPHONE NUMBERS:
Transportation
CHEMTREC: 800-424-9300 (U.S.)
703-527-3887 (International)
Non-transportation
Poison Hotline: 800-222-1222

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION
Benzyl alcohol	100-51-6	15-30%
Polyoxypropylenediamine	9046-10-0	15-30%
Amine terminated copolymer		
Triethylenetetramine (TETA)	112-24-3	
Phenalkamine curing agent	868765-93-9	< 25%
TETA, reaction products with phenol/formaldehyde	32610-77-8	
Polymer of epichlorohydrin, Bisphenol-A and DETA		< 10 %
2-hydroxyethyl ethers of CNSL	2322680-65-4	< 10%
Modified Polyamine	Proprietary	<5%
Hydroxybenzene	108-95-2	< 3%
Diethylenetriamine (DETA)	111-40-0	< 3%

(This product contains various filler powders in concentrations >1% that are regulated only as nuisance dusts. In this product they do not present a health hazard and consequently are not identified in this section.)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS Hazard Rating: Health - 3 Flammability - 1 Physical Hazards - 0
Danger! Corrosive. Severe eye, skin and respiratory irritant. May cause skin sensitization. Harmful if swallowed. Colorless gel with an ammonia-like odor.

PRIMARY ROUTE(S) OF ENTRY: Skin contact, eye contact, inhalation.

POTENTIAL HEALTH EFFECTS:

ACUTE INHALATION: Exposure to high concentrations of vapor causes irritation to the respiratory tract. Coughing and chest pain may result.

CHRONIC INHALATION: Prolonged or repeated exposure to high concentrations of vapors may cause lung tissue damage. Exposure to low vapor concentrations may cause a sore throat.

ACUTE SKIN CONTACT: Mildly corrosive. May cause severe irritation with pain.

CHRONIC SKIN CONTACT: Repeated contact may cause skin sensitization and dermatitis.

EYE CONTACT: Moderately corrosive. Causes severe irritation, pain and possible permanent injury. Vapor absorption into the eye can cause blurred vision and injury.

INGESTION: Moderately corrosive. May cause bleeding of the gastrointestinal tract. May cause burning of the mouth and throat. Aspiration hazard.

SYMPTOMS OF OVEREXPOSURE: Development of allergic reaction or sensitization. Skin irritation and redness. Respiratory irritation or tightness of chest. Conjunctivitis or corneal damage. Liver or kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:
Chronic respiratory disease (e.g., bronchitis, asthma). Skin conditions and allergies. Eye disorders.

4. FIRST AID MEASURES:

FIRST AID FOR EYES: Immediately flush with water for at least 15 minutes. Get prompt medical attention.

FIRST AID FOR SKIN: Remove contaminated clothing. Immediately wash skin with soap and water. Do not apply greases or ointments. Get medical attention if wide spread exposure.

FIRST AID FOR INHALATION: If symptoms occur as noted in Section 3, remove to fresh air. Get medical attention if symptoms persist or worsen.

FIRST AID FOR INGESTION: Give conscious person at least 2 glasses of water. Do not induce vomiting. If vomiting should occur spontaneously, keep airway clear. Get medical attention.

5. FIRE FIGHTING MEASURES:

FLASH POINT: > 200°F (PMCC)

EXTINGUISHING MEDIA: Water spray, dry chemical, alcohol foam and carbon dioxide (CO₂).

FIRE AND EXPLOSION HAZARDS: Burning will generate toxic fumes. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. If hardener is spilled into or mixed with sawdust, heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.

SPECIAL FIRE FIGHTING PROCEDURES: Use full-body protective gear and a self-contained breathing apparatus. If spill has ignited, use water spray to disperse vapors and protect personnel attempting to stop leak. Use water to cool fire-exposed containers.

6. ACCIDENTAL RELEASE MEASURES:

SPILL OR LEAK PROCEDURES: Stop leak without causing additional risk. Wear proper personal protective equipment. Contain spill and ventilate area. Large or small spill - scoop bulk into appropriate container for recovery. Use inert, non-combustible absorbent material (e.g., sand) and shovel remainder into suitable container for disposal. Do not use sawdust, wood chips or other cellulosic materials to absorb the spill, as the possibility for spontaneous combustion exists. Wash spill residue with warm, soapy water if necessary.

7. HANDLING AND STORAGE:

STORAGE TEMPERATURE (min./max.): 40°F (4°C) / 90°F (32°C)

STORAGE: Minimum feasible handling temperatures should be maintained. If stored above 100°F, nitrogen atmosphere is recommended. Keep containers tightly closed.

HANDLING PRECAUTIONS: Use only with adequate ventilation. Do not breath vapors or mists from heated material. Avoid contact with skin and eyes. Wash thoroughly after handling. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

EYE PROTECTION GUIDELINES: A minimum of safety glasses with side shields.

SKIN PROTECTION GUIDELINES: Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

RESPIRATORY/VENTILATION GUIDELINES:

General mechanical or local exhaust ventilation. In the absence of adequate ventilation, use a NIOSH approved air purifying respirator with an organic vapor cartridge.

Note: West System, Inc. has conducted an air sampling study using this product or similarly formulated products. The results indicate that the components sampled for (benzyl alcohol, phenol, formaldehyde and amines) were either so low that they were not detected at all or they were well below OSHA's permissible exposure levels.

MSDS #610B-08a

Last Revised: 09SEPT08

MSDS #610B-08a

Last Revised: 09SEPT08

ADDITIONAL PROTECTIVE MEASURES:..... Use where there is immediate access to safety shower and emergency eye wash. Provide proper wash/cleanup facilities for proper hygiene. Contact lens should not be worn when working with this material. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

OCCUPATIONAL EXPOSURE LIMITS:..... Not established for product as whole. Refer to OSHA's Permissible Exposure Level (PEL) or the ACGIH Guidelines for information on specific ingredients.

9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL FORM..... Gel.
COLOR..... Colorless.
ODOR..... Ammonia-like.
BOILING POINT..... > 480°F.
MELTING POINT/FREEZE POINT..... No data.
pH..... Basic.
SOLUBILITY IN WATER..... Appreciable.
SPECIFIC GRAVITY..... 1.036.
BULK DENSITY..... 8.67 lb/gal.
VAPOR PRESSURE..... < 1 mmHg @ 20°C.
VAPOR DENSITY..... Heavier than air.
% VOLATILE BY WEIGHT..... ASTM 2369-07 was used to determine the Volatile Matter Content of mixed epoxy resin and hardener. 610 Resin and 610 Hardener, mixed together at 2.13:1 by weight, has a density of 1102 g/L (9.20 lb/gal). The combined VOC content for 610 Resin / 610 Hardener is 11.80 g/L (0.10 lb/gal).

10. REACTIVITY:

STABILITY:..... Stable.

HAZARDOUS POLYMERIZATION:..... Will not occur.

INCOMPATIBILITIES:..... Strong oxidizers, acids, reactive organometallic compounds.

DECOMPOSITION PRODUCTS:..... Ammonia, oxides of nitrogen, carbon monoxide, carbon dioxide, and possibly aldehydes and ketones.

11. TOXICOLOGICAL INFORMATION:

No specific oral, inhalation or dermal toxicology data is known for this product.

Oral:..... Expected to be slightly toxic.
Inhalation:..... Expected to be slightly toxic.
Dermal:..... Expected to be slightly toxic.

CARCINOGENICITY:

NTP..... No.
IARC..... No.
OSHA..... No.

This product contains no known carcinogens in concentrations greater than 0.1%.

12. ECOLOGICAL INFORMATION:

No specific data. Wastes from this product may present long term environmental hazards. Do not allow into sewers, on the ground or in any body of water.

13. DISPOSAL CONSIDERATIONS:

WASTE DISPOSAL METHOD:..... Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods.

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION:

D.O.T. SHIPPING NAME:..... Polyamines, solid, corrosive, n.o.s.

TECHNICAL SHIPPING NAME:..... Polyoxypropylenediamine
D.O.T. HAZARD CLASS:..... Class 8
U.N./N.A. NUMBER:..... UN 3259
PACKING GROUP:..... PG III

15. REGULATORY INFORMATION:

OSHA STATUS:..... Corrosive; irritant; possible sensitizer.
TSCA STATUS:..... All components are listed on TSCA inventory or otherwise comply with TSCA requirements.

SARA TITLE III:

SECTION 313 TOXIC CHEMICALS..... This product contains phenol (hydroxybenzene) and is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

STATE REGULATORY INFORMATION:

The following chemicals are specifically listed or otherwise regulated by individual states. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME

/CAS NUMBER

CONCENTRATION

STATE CODE

Tetraethylenetriamine
112-24-3

<10%

FL, MA, NJ, PA

16. OTHER INFORMATION:

REASON FOR ISSUE:..... New Adhesive Hardener
PREPARED BY:..... G. M. House
APPROVED BY:..... G. M. House
TITLE:..... Health, Safety & Environmental Manager
APPROVAL DATE:..... September 9, 2008
SUPERSEDES DATE:..... NA
MSDS NUMBER:..... 610-08a

Note: The Hazardous Material Indexing System (HMIS), cited in the Emergency Overview of Section 3, uses the following index to assess hazard rating: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; and 4 = Severe.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of West System Inc. The data on this sheet is related only to the specific material designated herein. West System Inc. assumes no legal responsibility for use or reliance upon these data.